

509.00 EUR
incl. 19% VAT, plus [shipping](#)



Support:  [Specifications](#)

Chip	Broadcom
Dimensions	140x138x60mm
Certifications&Safety	CE, FCC, ROHS
I/O Ports	8x 10/100/1000BaseT(X) 4x 1000 BaseSFP RS-232(RJ45) Console port LED: Power, port speed, port connection
Management	Support WEB Interface IEEE802.3 10Base-T Ethernet standard IEEE802.3u 100Base-TX/FX IEEE802.3z 1000Base-X IEEE802.3ab 1000Base-T(X) IEEE802.3x Flow control
Standards	IEEE802.1d STP IEEE802.1w RSTP IEEE802.1s MSTP IEEE802.1p QoS IEEE802.1ad QinQ
Network interface / Wire specifications	10BASE-T: Category 3 and above non-mask / mask twisted pair (<=100 m) 100BASE-TX: Category 5 and above non-mask / mask twisted pair (<=100 m) 1000BASE-T: Category 5 and above non-mask / mask twisted pair (<=100 m)
PoE Support	No
Power input / consumption	Input voltage 12-36VDC Reverse connection protection Power interface : 5pin terminal
Operating temperature	-40~75°C
Cooling	Fanless
MTBF	100.000hrs