

419.00 EUR

incl. 19% VAT, plus [shipping](#)

- HBJC377F631W-3455B
- Realtek LAN



- Intel® Apollo lake Processor (TDP 10W)
- Support 1 * SO-DIMM DDR3L , up to 8GB memory
- 2 * USB2.0, 4 * USB3.0, 2 * DP, 2 * RJ45, 1 * SD, 1 * RS232 (RJ45 type)
- DC-12V_60W FSP Adapter

MB Model	<ul style="list-style-type: none"> - JNF631-3350 / 3.5" SBC - JNF631-4200 / 3.5" SBC
Part No.	<ul style="list-style-type: none"> - HBJC377F631-3350B (non-WIFI) / HBJC377F631W3350B (WIFI) - HBJC377F631-4200B (non-WIFI) / HBJC377F631W4200B (WIFI)
CPU/Chipset	- Intel® Apollo lake Processor N Series (TDP 10W)
Memory	- 1 * SO-DIMM slots DDR3L-1600MHz , up to 8GB
Storage	<ul style="list-style-type: none"> - 1 * 2.5" SATA3 6Gb/s internal drive bay (Max Height 9.5 mm) - 1 * M.2 SSD Device (M Key-2242) - 1 * Micro SD card slot
Network	<ul style="list-style-type: none"> - 2 * Realtek GbE - 1 * SIM Card Slot
Expansion	- 1 * full-size Mini-PCIe slot (for WiFi expansion)
Rear Panel I/O	<ul style="list-style-type: none"> - 4 * USB 3.0 - 2 * DP (Max. resolution:4096 x 2160@60Hz) - 2 * RJ45 - 1 * DC-In jack - 1 * RS232 (RJ45 type) - 1 * Micro SD - 1 * Audio (Line out + Mic)
Front Panel I/O	<ul style="list-style-type: none"> - 1 * Power button , 1 * Reset button - 1 * Power LED , 1 * HDD LED - 2 * USB 2.0 ports - 1 * Line-out - 2 * COM

Power Source	- FSP DC Adapter / AC 90~240V input / DC12V-5A-60W / LV6
Compliance	- CE, FCC, LVD, RoHS
Safety	- Vibration test: N.C - Shock test: N.C
Temperature	- Operating Temperature: 0 ~ 50° C - Storage Temperature: -10 ~ 70° C
Dimensions	- 185 (W) x 142 (D) x 48 (H) mm
Packing	- Net Weight: 1.4KG - Gross Weight: 2.4KG - Color Box dimension: 250 (W) * 118 (D) * 295 (H) mm
OS Support	- Windows 10, Linux
Warranty	- 2 Year limited warranty