



698.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Fanless Black Aluminum Enclosure
- Support Intel LGA1151 Coffee Lake Processors
- Supports DDR4-2133 SODIMM up to 32GB
- Supports up to 3 Displays, 1\* DMI, 2\* DP
- 1\* 2.5" SATA3 6Gb/s Internal Drive Bay
- 1\* M.2-2242/2260/2280 Slot for SSD
- Support Onboard TPM IC
- 120W 19V AC Adapter
- 264 (W) x 199.4 (D) x 58 (H) mm

|                    |                                                                                                                                                                                                                                                                                              |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MB Model           | – JNF797-Q370 Series/ MINI-ITX                                                                                                                                                                                                                                                               |
| Part No.           | – HBJC501F797-Q37-B (non-WIFI)<br>– HBJC501F797WQ37-B (WIFI)                                                                                                                                                                                                                                 |
| BIOS               | – AMI SMT Flash ROM                                                                                                                                                                                                                                                                          |
| CPU/Chipset        | – Intel® LGA1151 Coffee Lake Processor (Max. TDP 35W)<br>– Intel® Q370 chipset<br><b>Notes: When the system runs, CPU will automatically adjust its working clock frequency according to changing workload.</b>                                                                              |
| Memory             | 2 * SO-DIMM slots / dual channel DDR4-2400/2666 up to 32GB total                                                                                                                                                                                                                             |
| Storage            | – 1 * 2.5" SATA3 6Gb/s internal drive bay (only support 2.5" HDD with a height ≤ 10mm)<br>– 1 * M.2-2242/2260/2280 (M-KEY) slot for SSD                                                                                                                                                      |
| Network            | – 2 * Intel Gigabit LAN (i219LM, i211AT)<br>– 1 * M.2-2230 (E-KEY) slot for WIFI module expansion                                                                                                                                                                                            |
| Rear Panel I/O     | – 4 * USB 3.1 ports (Gen. 2)<br>– 1 * HDMI (Max Resolution: 4096 x 2160@30Hz)<br>– 2 * DP (Max Resolution: 4096 x 2304@60Hz)<br>– 2 * RJ45 (Intel GbE , 1 * i219-LM, 1 * i210-AT)<br>– 1 * Audio<br>– 2 * COM (RS232/422/485)<br>– 2 * Antenna holes (HBJC501F797WQ37-B only)<br>– 1 * DC-In |
| Front Panel I/O    | – 1 * Power button, 1 * HDD LED<br>– 2 * USB 2.0 ports                                                                                                                                                                                                                                       |
| Internal Expansion | – Support TPM1.2/2.0 (on board option)<br>– SIM card slot                                                                                                                                                                                                                                    |

|                |                                                                                                                                                               |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power Source   | – AC to DC Adapter 19VDC-6.3A 120W                                                                                                                            |
| Certifications | – CE, FCC, LVDS, RoHS, ErP Ready                                                                                                                              |
| Temperature    | – Operating Temperature: -20 ~ 50° C (The test environment is closed and windless)<br>– Storage Temperature: -10 ~ 70° C<br>– Humidity : 90% , non-condensing |
| Dimensions     | – 264 (W) x 199.4 (D) x 58 (H) mm                                                                                                                             |
| Packing        | – Net Weight: 4.2KG<br>– Gross Weight: 5KG<br>– Color Box dimension: 406 (W) * 148 (D) * 380 (H) mm                                                           |
| OS Support     | – Windows 10, Linux                                                                                                                                           |
| Warranty       | – 2 Year limited warranty                                                                                                                                     |