

999.00 EUR

incl. 19% VAT, plus [shipping](#)



- Intel® Apollo Lake SoC Processor
- 1\* DDR3L 1866MHz SODIMM up to 8 GB
- 4\* USB3.1, 2\* HDMI, 2\* RJ45, 1\* MIC/Line-out Combo, 1\* COM (RJ45 type)
- Operating Temperature: -40 ~ 70° C
- M/B Form Factor : uTX (117x112mm)
- DC-12V\_60W Adapter

|             |                                                                                                                                                                      |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MB Model    | – MT95-90                                                                                                                                                            |
| Part No.    | – HBFCT95-90B<br>– HBFCT95W-90B (WIFI)                                                                                                                               |
| BIOS        | – AMI Flash ROM                                                                                                                                                      |
| CPU/Chipset | – Intel® Apollo Lake SoC Processor (E3940 CPU TDP 9.5W)                                                                                                              |
| Memory      | – 1* DDR3L 1866MHz SO-DIMM up to 8 GB                                                                                                                                |
| Network     | – 2* Intel® i210AT GbE                                                                                                                                               |
| Storage     | – 1* M.2 M-key (2242) Support SATA interface                                                                                                                         |
| Expansion   | – 1* M.2 E-key (2230) Support USB2.0 & PCIe1 interface (for WiFi module installed)<br>– 1* M.2 B-key (3042) Support USB3.0 interface (for 3G/4G/5G module installed) |

|                 |                                                                                                                                                                                                                                                                                                                    |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rear Panel I/O  | <ul style="list-style-type: none"> <li>– 2* USB3.1 (Gen1)</li> <li>– 2* HDMI (Max. Resolution: 3840 x 2160@30Hz)</li> <li>– 2* RJ45</li> <li>– 1* MIC/Line-out Combo (Realtek® ALC662VD)</li> <li>– 1* COM (RJ45 type)</li> <li>– 2* Antenna holes (WiFi only)</li> <li>– 1* DC-in jack (Lockable type)</li> </ul> |
| Front Panel I/O | <ul style="list-style-type: none"> <li>– 1* Power button</li> <li>– 1* Power LED, 1* HDD LED, 2* LAN LED</li> <li>– 2* USB3.1 (Gen1)</li> <li>– 1* AT / ATX mode Switch</li> </ul>                                                                                                                                 |
| Power Source    | <ul style="list-style-type: none"> <li>– AC to DC Adapter / AC 90~240V_DC12V_5A_60W</li> <li>– MT95-90 MB_DC 12V input</li> </ul>                                                                                                                                                                                  |
| Compliance      | – CE, FCC, LVD, RoHS, ErP Ready                                                                                                                                                                                                                                                                                    |
| Temperature     | <ul style="list-style-type: none"> <li>– Operating Temperature: -40 ~ 70° C (Under the condition of using M.2 interface SSD)<br/>(The test environment is closed and windless)</li> <li>– Storage Temperature: -40 ~ 80° C</li> <li>– Humidity: 10% ~ 90% RH @40°C (non-condensing)</li> </ul>                     |
| Dimensions      | – 144 (W) x 116.9 (D) x 65 (H) mm                                                                                                                                                                                                                                                                                  |
| OS Support      | – Windows 10, Linux                                                                                                                                                                                                                                                                                                |