



1469.00 EUR
incl. 19% VAT, plus [shipping](#)

- Intel Tiger Lake !
- i5-1135G7 !
- 17" Panel Computer !

- 17.0" 350 nits TFT LCD with LED backlight
- 10 points Multi Capacitive Touch
- Support Open frameless design
- A true Flat, easy to clean front surface with edge to edge design
- Front IP65 for protection against water and dust
- Aluminum Die-Cast Panel PC series, support for easy HDD and DARM installation
- Support Cable less design
- 12 36V DC input Support, with Electrical Over Stress(EOS), OVP design
- VESA Support 100x100mm

Model	- HPC170C-DCP1135G7	
Main System	- Intel® Tiger Lake i5-1135G7 2.4GHz/QC processor - 2* DDR4 SO-DIMM (Max 64GB) - 256MB SPI Flash ROM - Watchdog Timer 256 levels, 0~255 sec.	

Display	<ul style="list-style-type: none"> - IP65, NEMA 4 rugged protection, metal front bezel - 17.0" With LED Backlight - 350 nits - 16.7m display color - 1280 x 1024 @60Hz resolution - 170°/160° viewing angle (H/V) - 0.264 x 0.264mm pixel pitch - 4:3 aspect ratio - 1000:1 contrast ratio - 3.5ms response time
Touch Screen	<ul style="list-style-type: none"> - Projected capacitive type - 372.92 x 305.34mm ±0.3mm active range - Transparency ■ 85% - Surface Hardness ■ 6H (JIS-5400)
I/O Connector	<ul style="list-style-type: none"> - 2* USB3.2 (Gen. 2) - 4* USB2.0 - 2* RS232/422/485 - 2* RS232 (option 16bit GPIO) - 1* HDMI - 1* AT/ATX Mode Button - 2* RJ45 (1* Intel® I225-V 2.5GbE, 1* Intel® I219LM GbE) - 1* 12~36V DC-in Locking Jack - 1* Power button - 1* 2pin Front Power button
Storage	<ul style="list-style-type: none"> - 1* 2.5" SATA HDD - 1* M.2 M key (2242/2280, PCI-Ex4)
Expansion	<ul style="list-style-type: none"> - 1* M.2 E key (2230) for WIFI - 1* M.2 B key (3042/3052/6570) for 4G/5G Module (4pcs Built in Antenna)
Case	<ul style="list-style-type: none"> - Aluminum panel - Iron case - White color - Spray paint coating requirement
Power	<ul style="list-style-type: none"> - AC version: 100~240V AC-DC 60W power adapter or - DC version: 12VDC with over current protection fuse - Consumption: 47.5W
Compliance	<ul style="list-style-type: none"> - CE, FCC, IP65 (Front), Option
Safety	<ul style="list-style-type: none"> - Shock: 1ms duration - Vibration: 5~500Hz/1 Grms
Dimensions	<ul style="list-style-type: none"> - 400.9 x 333.3 x 65.0mm
Temperature	<ul style="list-style-type: none"> - Operating Temperature: -10 ~ 60° C - Storage Temperature: -20 ~ 70° C - Humidity: 10% ~ 90% RH @40°C (non-condensing)