

4869.00 EUR

incl. 19% VAT, plus [shipping](#)

- NVidia Orin Nano !
- 32GB RAM !
- IP66 !



- NVIDIA® Jetson AGX Orin™ SoM with 1792 CUDA Cores
- IP66 Design (Waterproof and Dustproof) for Harsh Environment
- 1 x 10 GbE, 2 GbE with PoE via Phoenix Contact® M12 IP67 Connectors
- 2 x CAN FD
- 2 x RS-232/422/485\*, 4 x DI/4 x DO\*
- Supporting 4 x GMSL-2 Cameras (via FAKRA Connectors)
- 9 ~ 60VDC Input with Built-in Smart Ignition Power Management
- -25 ~ 70°C Operating with Fanless Design
- Patented Design of Emergency Backup Battery (**Optional!**)

#### System

•

NVIDIA® Jetson AGX Orin™ 32GB – 200 TOPS

#### Module

(1792 CUDA® cores GPU + 8-core Arm Cortex-A78AE CPU + 32 GB LPDDR5)

#### Security

Security Boot, Arm TrustZone

|                          |  |                                                                                                                                                                                                                                                                                                     |
|--------------------------|--|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                          |  | <ul style="list-style-type: none"> <li>- 1 x 10GbE, 2 x 2.5GbE w/ 2 x IEEE 802.3at PoE PSE Class 4 (PoE+ 30 watts)<br/>(3 x Phoenix Contact® M12 X-coded connectors)</li> </ul>                                                                                                                     |
|                          |  | <ul style="list-style-type: none"> <li>- 2 x USB Type-A/IP67 connector for USB 3.2<br/>* One port share 10Gbps bandwidth</li> </ul>                                                                                                                                                                 |
|                          |  | <ul style="list-style-type: none"> <li>- 1 x HDMI Type-A/IP67 connector for HDMI 2.1 output</li> </ul>                                                                                                                                                                                              |
|                          |  | <ul style="list-style-type: none"> <li>- 1 x HD Audio from the HDMI</li> </ul>                                                                                                                                                                                                                      |
| Interface                |  | <ul style="list-style-type: none"> <li>- 1 x M12 A-coded connector for RS-232/422/485</li> <li>- 2 x M8 A-coded connectors for CAN FD</li> <li>- 1 x USB Type-C for System Recovery (Device only)</li> <li>- 4 x FAKRA-Z connectors for GMSL-2 cameras</li> <li>- 1 x Nano SIM card slot</li> </ul> |
|                          |  | <ul style="list-style-type: none"> <li>• 1 x M.2 3042/52 Key B slot (USB3.0) with a Nano SIM Card Slot</li> <li>• 1 x M.2 2230 Key E slot</li> <li>• * Thermal solution is required for M.2 5G Module</li> <li>• 1 x mPCIc Full size slot (USB.2.0 supported)</li> </ul>                            |
| INTERNAL EXPANSION       |  |                                                                                                                                                                                                                                                                                                     |
|                          |  | <ul style="list-style-type: none"> <li>• 1 x 64GB eMMC (Built-in within SoM)</li> <li>• 1 x M.2 2280 Key M slot supports NVMe SSD (Pre-installed)</li> </ul>                                                                                                                                        |
| STORAGE (Internal)       |  |                                                                                                                                                                                                                                                                                                     |
| Operating System / SDK   |  | NVIDIA® JetPack including Jetson Linux, NVIDIA® development tools                                                                                                                                                                                                                                   |
|                          |  | 25°C ~ 70°C w/0.6 m/s airflow (for barebone system)                                                                                                                                                                                                                                                 |
| Operating Temp.          |  | *Operating Temperature Varies by Accessories Installed.                                                                                                                                                                                                                                             |
|                          |  | -40 ~ 85°C                                                                                                                                                                                                                                                                                          |
| Storage Temp.            |  |                                                                                                                                                                                                                                                                                                     |
| Relative Humidity        |  | 10% RH – 90% RH (non-condensing)                                                                                                                                                                                                                                                                    |
| Certification / Standard |  | CE, FCC Class A, E-Mark, ECE R118, EN50155*, EN45545-2 (R25) *On going                                                                                                                                                                                                                              |
|                          |  | •                                                                                                                                                                                                                                                                                                   |
| Vibration                |  | <ul style="list-style-type: none"> <li>• MIL-STD-810H, Method 514.6, Procedure I, Cat.4 (Operating)</li> <li>• IEC60068-2-64, random, 2.5G@5~500Hz, 1hr/axis</li> </ul>                                                                                                                             |
| Shock                    |  | MIL-STD-810H, Method 516.6, Procedure I,<br>Trucks and semi-trailers=15G (11ms) with SSD (Operating)                                                                                                                                                                                                |
| Ingress Protection       |  | IP66                                                                                                                                                                                                                                                                                                |
| Power Input              |  | <ul style="list-style-type: none"> <li>• 1 x Phoenix Contact® M12 K-coded connector for DC-IN 9~60V<br/>Aluminum Alloy</li> </ul>                                                                                                                                                                   |
|                          |  | Fanless Passive Cooling Design                                                                                                                                                                                                                                                                      |
| Mechanical               |  | Wall Mount                                                                                                                                                                                                                                                                                          |
|                          |  | 5100 g                                                                                                                                                                                                                                                                                              |
|                          |  | 300 mm (L) x 190 mm (W) x 77,5 mm (H)                                                                                                                                                                                                                                                               |